

POLY-CLASSIC® DGL Dura GlassTM Columns

- **EASY TO CUT AND INSTALL**
- **DECAY RESISTANT**
- LOW MAINTENANCE
- LIGHTWEIGHT COLUMNS

- **IMPACT RESISTANT**
- LIMITED LIFETIME WARRANTY
- READY TO PRIME AND PAINT


| 20 800-423-3311

LIGHTWEIGHT FIBERGLASS COLUMNS EASILY HANDLE THE LOAD

Sometimes the most beautiful solutions are the most simple. Poly-Classic® DuraGlass™ square columns from Turncraft offer the classic beauty that homeowners and commercial property owners appreciate. Made from lightweight fiberglass, these columns are easy to cut, easy to install, and strong enough to carry heavy loads. Like other Poly-Classic® columns, DuraGlass™ columns are decay resistant and require little maintenance.

PLAN TYPES

Poly-Classic® Duraglass™ Columns are available in the following plan types. Please specify when you order. (Fractional components shown are typical. Customer may specify actual returns, wall thicknesses, etc.)



TIMESAVER FOR 8" NON-TAPERED COLUMNS

New to the Turncraft product line is our 8" square TimeSaver cap and base product. This new cap and base employs the same quick-fit installation as our round 8", 10", and 12" TimeSaver. Our TimeSaver cap and base

offers the easiest and quickest installation in the industry.


Customers claim: "The TimeSaver cap and base has cut our installation time in half."






DURAGLASS™ TAPERED SQUARE BUNGALOW COLUMNS

Bottom Width >	Shaft B	ottom	Shaft	:Тор	Space / Inside			
Top Width x Height	Outside Width	Inside Width	Outside Width	Inside Width	For Round	For Square	Load Capacity	
XTIOIGH	(A)	(B)	(D)	(C)	Support	Support	*	
10" > 6" x 5'			5 5/8"	5"	4 1/2"	4 1/2"		
10" > 6" x 6'	9 5/8"	9"					10,000	
10" > 6" x 8'	9 3/6			3	4 1/2		10,000	
10" > 6" x 10'								
12" > 8" x 5'		11"	7 5/8"	7"	6 1/2"	6 1/2"		
12" > 8" x 6'	11 5/8"						10.000	
12" > 8" x 8'	11 3/0						10,000	
12" > 8" x 10'								
16" > 12" x 5'								
16" > 12" x 6'	15 5/8"	15	11 5/8"	11"	10 1/2"	10 1/2"	10.000	
16" > 12" x 8'	10 0/0	15	113/6	11	10 1/2	10 1/2	10,000	
16" > 12" x 10'								



^{*} Load capacities are reduced when loads are not centered. Split columns are not load bearing, even when re-assembled.








BUNGALOW CAP AND BASE SPECS

	Column		Bungalo	ow Base		Bungalow Cap				
Column Nominal	Inside Top	Plat	form	Moulding	Height	Height Platform		Moulding	Height	
Width †	Width (maximum)	Α	В	С	В-С	D	Е	F	E-F	
10"	5"	13 5/8"	1"	1 1/4"	2 1/4"	9 5/8"	1"	1 1/8"	2 1/8"	
12"	7"	15 5/8"	1"	1 1/4"	2 1/4"	11 5/8"	1"	1 1/8"	2 1/8"	
16"	11"	19 5/8"	1"	1 1/4"	2 1/4"	15 5/8"	1"	1 1/8"	2 1/8"	


 $[\]dagger$ Net size is approximately 3/8" less than nominal.



PULTRUDED TUSCAN CAP AND BASE SPECS

	Column		Pultrude	d Tuscar	n Base		Pultruded Tuscan Cap				
Column Nominal			Plinth		Torus		Echinus	Abacus		Height	
Width	Width										
T T	(maximum)	Α	В	С	D	B-D	F	E	D	E-F	
10"	5"	13 1/8"	1 11/16"	1 5/8"	3/8"	3 11/16"	1 3/8"	1 7/16"	8 1/2"	2 13/16"	
12"	7"	15 1/8"	1 11/16"	1 5/8"	3/8"	3 11/16"	1 3/8"	1 7/16"	10 1/2"	2 13/16"	
16"	11"	19 1/8"	1 11/16"	1 5/8"	3/8"	3 11/16"	1 3/8"	1 7/16"	14 1/2"	2 13/16"	


[†] Net size is approximately 3/8" less than nominal.



| 22 800-423-3311

DURAGLASS™ NON-TAPERED SQUARE

	Shaft Bo	ottom	Shaft	Тор	Space Availa			
Column Nominal	Outside Width	Inside Width	Shaft Neck ‡	Astragal Ring	For Round	For Square	Load Capacity lbs.	
Width †	A	В	С	D	Support	Support		
8"	7 5/8"	7 1/8"	4 1/2"	3/4"	6 3/4"	6 3/4"	5,000	
10"	9 5/8"	9 1/8"	5"	3/4"	8 3/4"	8 3/4"	6,000	
12"	11 5/8"	11 1/8"	5 1/2"	3/4"	10 3/4"	10 3/4"	7,000	
14"	14"	11 3/4"	Adjustable	1 7/8"	11 1/2"	11 1/2"	10,000	
16"	16"	13 3/4"	Adjustable	1 7/8"	13 1/2"	13 1/2"	10,000	
18"	18"	15 3/4"	Adjustable	1 7/8"	15 1/2"	15 1/2"	10,000	
20"	20"	15 3/4"	Adjustable	1 7/8"	15 1/2"	15 1/2"	10,000	



† Actual shaft net widths may vary from nominal size shown.

‡ Necking is shipped loose for pultruded columns. Spacing shown is typical, but may be adjusted by the installer.

	Available Heights										
Widths	6'	8'	9'	10'	12'	14'	16'	18'	20'	22'	24'
8"	✓	✓	✓	✓	✓						
10"	✓	✓	✓	✓	✓						
12"	✓	✓	✓	✓	✓						
14"		✓	✓	✓	~	✓	✓	✓	✓	~	✓
16"		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
18"		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
20"		✓	✓	✓	~	✓	✓	✓	✓	~	✓

The "Space Available Inside Shaft" measurements are calculated at the top inside width (with 3/8" to 3/4" tolerance), when using Tuscan caps.

When composite ornamental capitals are used, the neck sleeve will reduce the inside available space significantly.

If the column will not be required to carry a load, it may be possible for the installer to modify or remove the neck sleeve to allow more interior space. Please contact Turncraft Customer Service for more information.

These measurements are provided to assist in determining the correct column width to go around a load bearing post or lally column, or for clearance for water downspouts, conduits, etc.


TIMESAVER TUSCAN CAP AND BASE WITH NECK MOULDING

						T	uscan Bas	se		Tuscan Cap						
Nc	ominal	Net Outside	Shaft Inside		Pli	nth	То	rus	Height	Ne	ck	Echinus	Ab	acus	Height	
	Vidth	Width	Width	Material	А	В	С	D	B-D	E	F†	G	Н	1	G-H	
	8"	7 5/8"	7 1/8"	ABS	10 9/16"	1 3/4"	1 5/8"	1/2"	3 7/8"	1 1/2"	1 3/4"	1 5/16"	1 3/8"	10 11/16"	2 11/16"	
	10"	9 58"	9 7/8"	ABS	13 1/2"	2 3/8"	2 1/8"	3/4"	5 1/4"	1 1/2"	1 1/2"	1 13/16"	1 3/4"	13 1/4"	3 9/16"	

[†] Customer applies neck moulding. They can adjust the F dimension (necking position) as desired. Dimensions shown match the round FRP shafts.

POLYURETHANE TUSCAN CAP AND BASE WITH NECK MOULDING

					Tu	scan Bas	е		Tuscan Cap					
Nominal	Net Shaft Nominal Outside Inside			Plir	nth	Toru	ıs	Height	N€	eck	Echinus	Aba	cus	Height
Width	Width	Width	Material	Α	В	С	D	B-D	Е	F†	G	Н		G-H
8"	7 5/8"	7 1/8"	Polyurethane	11 3/8"	1 7/8"	1 3/4"	5/8"	4 1/4"	1 1/2"	1 3/4"	1 5/16"	1 3/8"	11 1/4"	2 3/4"
10"	9 5/8"	9 1/8"	Polyurethane	13 1/2"	2 3/8"	2 1/8"	3/4"	5 1/4"	1 1/2"	1 1/2	1 13/16"	1 3/4"	13 1/4"	3 9/16"
12"	11 3/4"	11 1/4"	Polyurethane	17"	2 3/4"	2 3/8"	7/8"	6"	1 7/8"	5/8"	1 7/8"	2"	17 1/4"	3 7/8"
14"	14"	11 3/4"	Poly‡	19"	3 3/8"	2 15/16"	1"	7 5/16"	2"	2 3/16"	2 11/16"	2 5/16"	19 3/4"	5"
16"	16"	13 3/4"	Poly‡	21 7/8"	3 7/8"	3 3/8"	1 1/8"	8 3/8"	2"	2 1/4"	2 13/16"	2 3/4"	22 1/4"	5 9/16"
18"	18"	15 3/4"	Poly‡	24 5/8"	4 1/4"	3 7/8"	1 1/2"	9 5/8"	2"	2 1/4"	3"	3"	25"	6"
20"	20"	17 3/4"	Poly‡	27 3/8"	4 3/4"	4 1/4"	1 3/4"	10 3/4"	2 3/16"	2 3/4"	3 1/8"	3 3/8"	27 3/4"	6 1/2"



[†] Customer applies neck moulding. They can adjust the F dimension (necking position) as desired. Dimensions shown match the round FRP shafts.

OPTIONAL CRAFTSMAN CAP AND BASE

Column	Craftsm	an Base	Craftsman Cap				
Width	Height	Width (A)	Height	Width (A)			
8"	9 1/4"	8 15/16"	7 1/4"	8 15/16"			
10"	9 1/4"	10 15/16"	7 1/4"	10 15/16"			
12"	9 1/4"	13 1/16"	7 1/4"	13 1/16"			

9 1/4"

7 1/4"

No installation hardware included. Sold as sets only. No necking. Made of PVC to match the Craftsman Series columns.

[‡] Cap, Base and Necking for 14" and larger columns ship as lineal parts, mitered, to assemble around the column.